

STROBOSCOPE

Microprocessor Based, High Accuracy



DS-3200 / DS-2200

Keyboard Operating

Wide Range, High Accuracy

Range: 60.0 to 30,000 RPM/FPM

Resolution: 0.1 FPM below 2,000

1 FPM above 2,000

Lamp: Xenon flash tube

Display: 5 digits LED

Special Function: $\times 2$, $\div 2$,

3 Setup memory

Accuracy: $\pm 0.01\%$

Temp. Drift: $\pm 0.01\%$

Power Supply: AC100V / AC110V

AC220V / AC240V

Power Consumption:

Approx. 25 Watts

Operating Temp.: 0 – 40°C

32 – 104°F

Operating Humidity:

Below 85% RH.

Dimension: 115 x 115 x 200 mm

(Not including handle)

Weight: Approx. 1.5 Kgs / 3.3 Lbs.



SAGA ELECTRONIC ENTERPRISE CO., LTD.

4F, No.56, LANE 31, MINZU ROAD, DANSHUI,
NEW TAIPEI CITY, TAIWAN 251-67

TEL: 886-2-8809 2338 FAX: 886-2-8809 2445

<http://www.saga-electronic.com>

email: sagaleu@ms8.hinet.net

STROBOSCOPE

閃光同步測頻儀轉速計



DS-3200 / DS-2200

按鍵式操作

測量範圍廣、精確度高

範圍：60.0 – 30,000 RPM/FPM

解析度：0.1 FPM 2,000 以下

1 FPM 2,000 以上

燈泡：Xenon 燈管

顯示器：5 位數紅色 LED 顯示

特殊功能：×2, ÷2, 三組記憶

精確度：±0.01%

溫度飄移：±0.01%

電源：AC100V / AC110V /

AC220V / AC240V

消耗功率：大約 25 瓦

使用溫度範圍：攝氏 0 - 40 度

華氏 32 - 104 度

使用濕度：相對溼度 85% 以下

尺寸：115 x 115 x 200 mm

(不含把手)

重量：大約 1.5 公斤 / 3.3 磅

選購附件：手提箱 DS-CASE

閃光燈管 DS-FT-01



台益電子企業股份有限公司

251-67 新北市淡水區民族路 31 巷 56 號 4 樓

TEL: 886-2-8809 2338 FAX: 886-2-8809 2445

<http://www.saga-electronic.com>

email: sagaleu@ms8.hinet.net

APPLICATION 應用

STROBOSCOPE/TACHOMETER that is ideal for inspecting and measuring the speed of moving gears, fans, pumps, motors, grinders and virtually all processing equipment used in general industrial maintenance, production, quality control, laboratories and as well as for school and colleges for demonstrating strobe action.

閃頻測速儀(轉速計)非常適合使用在檢查以及測量轉動中的齒輪,風扇,幫浦,馬達,研磨器,以及實際上設備處理,用於一般工業維護,生產,品質控制及實驗室,或學校閃光原理的教學。

SPECIFICATION 規格說明

Model	型號	DS-3200	DS-2200
Operating	操作方式	Keyboard operating 全按鍵式操作	
Range	使用範圍	60.0 - 30,000 rpm/fpm	60.0 - 18,000 rpm/fpm
Resolution	解析度	0.1 rpm/fpm below 2,000 rpm (0.1 rpm/fpm 低於 2,000 rpm 時) 1 rpm/fpm above 2,000 rpm (1 rpm/fpm 高於 2,000 rpm 時)	
Display	顯示器	5 digits LED, 10mm High 5 位數, 字高 10mm	
Setup Accuracy	精確度	± 0.01%	
Temp. Drift	溫度飄移	± 0.01%	
Lamp	閃光燈炮	Xenon flash tube	
Special Function	特別功能	×2, ÷2 Three complete setup memory 三組轉速記憶設定 (M1, M2, M3) Four speed rate adjustment 四種調整速度 (Fast, Middle, Slow, Fine)	
Power Supply	使用電源	AC110V or AC220V±10%, 50/60 Hz Please specify voltage when placing orders. AC100V, AC110V, AC220V, AC240V 訂購時特別註明使用電壓	
Power Consumption	耗電	Approximately 25 Watts (Full range) 大約 25 瓦	
Operating Temp./Humidity	使用溫度/溼度限制	0 to 40°C (32 to 104°F) 攝氏 0-40 度 (華氏 32-104 度) Humidity below 85% 濕度以下	
Dimension	外觀尺寸	115 x 115 x 200 mm without removable handle 不含活動式把手	
Weight	重量	Approx. 1.5 Kgs / 3.3 Lbs 大約 1.5 公斤 / 3.3 磅	
Standard Accessories	標準配件	AC power cord, Xenon Tube, Operation Manual 電源線, 閃光燈管, 使用說明書	
Optional Accessories	選購附件	Carrying Case (DS-Case) 手提箱 Xenon Flash Tube (DS-FT-01) 閃光燈管	

* Appearance and specification listed in this brochure are subject to change without notice.

以上規格如有變更恕不另行通知

DISTRIBUTOR 經銷商

